

C7

High capacity precision screening with the triple deck C7, available with interchangeable screen meshes on each deck. Standard the best service access and walkways around all sides of the screenbox. Fast set up time and no support legs.

Standard walkways on all sides of the screenbox

Maintenance free bearings on main and side conveyors (greased for life)

Tipping grid can move to vertical position

Triple deck screenbox

- Feed hopper of HB 450 steel
- Increased uptime due to Long Life Grease
- Superiour level of surface treatment
- Accessable doors and panels on all sides of the machines for easy maintenance and repair

14
t/h

Diesel-hydraulic

Applications

Quarrying 0-4, 4-8, 8-16, 16-32 and others
Separation of aggregate
Sand and gravel
Construction and demolition waste
Screening behind a crusher
Coal
And others

METRIC



Technical specifications	
Capacity up to	400 t
Weight 3-deck	34,8 t
Screen box (lxw)	5450 x 1800 mm
Feed hopper in HB450	8 m³
Hydraulic adjustable grid angle	13, 14, 18,24 & 28°
Grid opening possibilities	100, 122, 135 & 150 mm
Loading height	
feeding height with tipping grid	3060 - 3520 mm
feeding height without tipping grid	2400 mm
Side loading length	4500 mm
Beltfeeder with adjustable speed (l x w)	3467 mm x 1200 mm
Main conveyor (l x w)	10700 mm x 1200 mm
Screen box l x w	5450 x 1800 mm
Upper deck m²	9,8 m²
Middle deck m²	9,8 m²
Lower deck m²	9,4 m²
Adjustable screen inclination	9 - 24°
Standard walkway beside screenbox	Left & Right side & front
Standard Long Life Grease: grease interval	Every 100h
Conveyor belts (l x w) & discharge height	
Underscreen conveyor/ fine fraction (discharge height)	6750 mm x 1200 mm
Stockpile conveyor left (middle fraction fine)	10000 mm x 800 mm
Stockpile conveyor right (middle fraction coarse)	10000 mm x 800 mm
Belt conveyor reversible (coarse fraction) - 3-deck	1700 mm x 650 mm
Stockpile conveyor left (coarse fraction) - 3-deck	6875 mm x 650 mm
Track-unit: Length, total width, track shoe width	4076, 2550, 450 mm
2-speed track drive	1,32 km/h and 2,28 km/h
Engine unit(s) 1500/1800 RPM	79 kW/88 kW
Control	PLC – IP 67 LCD screen 4,3" & remote control
Smart sequential auto start/stop from remote control	•
Available drive systems	
Diesel/hydraulic drive	•
ZERO drive (no combustion engine, plug-in electric)	planned in near future

OPTIONS

Feeding & screening	
Wear lining in hopper HB 450: 5 mm	•
Hopper extensions	hopper extensions 13m³
Feeding width extensions (total feeding length)	5120 mm
Anti clogging system	•
Wide range of screen media	•
Washing screen option, multiple water lines on each deck, without under screen conveyor but with suspension discharge container	4500 x 1800 mm ??? 72 water nozzles ???
Second level walkway on left and right side of the screenbox	???
Vibrating grid, double deck: 0, 5, 10, 15, 20°, top deck: grizzly, 5,5m² bottom deck: wire mesh, 5,1 m²	•
Conveyors	
Overband magnet on main conveyor	•
Magnetic drum and discharge chute	•
Belt Cover on main conveyor and under screen conveyor	•
Telescopic conveyor for coarse fraction l x w, on 3-deck version	11600 mm x 650 mm
Tungsten scrapers on main conveyor and under screen conveyor	•
Other options	
Radio remote	•
Working lights	•
Fuel filling pump	•
Heating system for engine unit: diesel and hydraulic tank	•
Telematics system UMTS/GPS	•
Lifting eyes	•

TRANSPORT	
Transport l x w x h (mm) 3-deck	15380 x 3200 x 3430

LEGENDA	
•	applicable - available
/	not applicable- not available

METRIC



C7

High capacity precision screening with the triple deck C7, available with interchangeable screen meshes on each deck. Standard the best service access and walkways around all sides of the screenbox. Fast set up time and no support legs.

Standard walkways on all sides of the screenbox

Maintenance free bearings on main and side conveyors (greased for life)

Tipping grid can move to vertical position

Triple deck screenbox

3,69

US Gal/h

Diesel-hydraulic

Applications

Quarrying 0-4, 4-8, 8-16, 16-32 and others
 Separation of aggregate
 Sand and gravel
 Construction and demolition waste
 Screening behind a crusher
 Coal
 And others

- Feed hopper of HB 450 steel
- Increased uptime due to Long Life Grease
- Superiour level of surface treatment
- Accessable doors and panels on all sides of the machines for easy maintenance and repair

IMPERIAL



Keestrack

Technical specifications	
Capacity up to	440 sT
Weight 3-deck	38,3 sT
Screen box (lxw)	17'11"
Feed hopper in HB450	10 yard ³
Hydraulic adjustable grid angle	13, 14, 18,24 & 28°
Grid opening possibilities	4", 5", 5,5" & 6"
Loading height	
feeding height with tipping grid	10'1" - 11'6"
feeding height without tipping grid	7'10"
Side loading length	14'9"
Beltfeeder with adjustable speed (l x w)	11'5" x 3'11"
Main conveyor (l x w)	35'1" x 3'11"
Screen box l x w	17'11" x 6'
Upper deck m²	9,8 m²
Middle deck m²	9,8 m²
Lower deck m²	9,4 m²
Adjustable screen inclination	9 - 24°
Standard walkway beside screenbox	Left & Right side & front
Standard Long Life Grease: grease interval	Every 100h
Conveyor belts (l x w) & discharge height	
Underscreen conveyor/ fine fraction (discharge height)	22'2" x 3'11"
Stockpile conveyor left (middle fraction fine)	32'4" x 2'8"
Stockpile conveyor right (middle fraction coarse)	32'4" x 2'8"
Belt conveyor reversible (coarse fraction) - 3-deck	5'7" x 2'2"
Stockpile conveyor left (coarse fraction) - 3-deck	22'6" x 2'2"
Track-unit: Length, total width, track shoe width	13'4", 8'4", 1'6"
2-speed track drive	0,8 / 1,5 mph
Engine unit(s) 1500/1800 RPM	79 kW/88 kW
Control	PLC – IP 67 LCD screen 4,3" & remote control
Smart sequential auto start/stop from remote control	•
Available drive systems	
Diesel/hydraulic drive	•
ZERO drive (no combustion engine, plug-in electric)	planned in near future

OPTIONS

Feeding & screening	
Wear lining in hopper HB 450: 5 mm	•
Hopper extensions	hopper extensions 17yard ³
Feeding width extensions (total feeding length)	16'10"
Anti clogging system	•
Wide range of screen media	•
Washing screen option, multiple water lines on each deck, without under screen conveyor but with suspension discharge container	14'9" x 5'11" ??? 72 water nozzles ???
Second level walkway on left and right side of the screenbox	???
Vibrating grid, double deck: 0, 5, 10, 15, 20°, top deck: grizzly, 5,5m² bottom deck: wire mesh, 5,1 m²	•
Conveyors	
Overband magnet on main conveyor	•
Magnetic drum and discharge chute	•
Belt Cover on main conveyor and under screen conveyor	•
Telescopic conveyor for coarse fraction l x w, on 3-deck version	38' x 2'2"
Tungsten scrapers on main conveyor and under screen conveyor	•
Other options	
Radio remote	•
Working lights	•
Fuel filling pump	•
Heating system for engine unit: diesel and hydraulic tank	•
Telematics system UMTS/GPS	•
Lifting eyes	•

TRANSPORT	
Transport l x w x h (mm) 3-deck	15380 x 3200 x 3430

LEGENDA	
•	applicable - available
/	not applicable- not available

